

**Prüfbericht 22-00097-CX-GBM-02**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058**

**ANLAGE: 9.6**  
 Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18  
 Stand: 17.07.2023



Auto Service

Seite: 1 von 4

**Manufacturer : SEAT, SKODA, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 5 J X 14 H2 Off set(mm) : 35  
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

**Technical dates, short form**

| version | Version name         |                          | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
|         | Wheel identification | Centering identification |                     |                    |                             |  |                            |
| R1-1829 | R1-1829              | Without                  | 57                  |                    | 405                         | 1793                                   | 05/22                      |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : SEAT**

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

Tightening torque for fixing parts : 110 Nm

commercial type: **MII**

| Vehicle type | Approval            | kW      | Tires        | Restrictions of tires | Restrictions  |
|--------------|---------------------|---------|--------------|-----------------------|---|
| AA           | e13*2007/46*1168*.. | 44 - 55 | 165/70R14    | 12K; 51G              | 10B; 11H; 11N; 51A; 744; 76V; 77E; BF2; 1); 2); 33) |
|              |                     |         | 175/65R14    | 51G                   |   |
| AA           | e13*2007/46*1168*.. | 44 - 55 | 165/70R14    |                       | 744; 77E; BF2; 1); 2); 33)                          |
|              |                     |         | 175/65R14    |                       |   |
|              |                     | 61      | 165/70R14    |                       |   |
| AAN          | e13*2007/46*1183*.. | 55      | 165/70R14 81 |                       | BF2; 1); 2); 33)                                    |
|              |                     |         | 175/65R14 82 |                       |   |
| AAN          | e13*2007/46*1183*.. | 44 - 55 | 165/70R14    |                       | 744; BF2; 1); 2); 33)                               |
|              |                     |         | 175/65R14    |                       |   |

**Manufacturer : SEAT, SKODA, VOLKSWAGEN**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : SKODA**

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

commercial type: **CITIGO**

| Vehicle type | Approval            | kW      | Tires         | Restrictions of tires | Restrictions               |
|--------------|---------------------|---------|---------------|-----------------------|----------------------------|
| AA           | e13*2007/46*1169*.. | 44 - 55 | 175/65R14     |                       | 744; 77E; BF2; 1); 2); 33) |
|              |                     |         | 165/70R14     |                       |                            |
|              |                     |         | 165/70R14 M+S |                       |                            |
| AA           | e13*2007/46*1169*.. | 44 - 55 | 165/70R14     |                       | 744; 77E; BF2; 1); 2); 33) |
|              |                     |         | 165/70R14 M+S |                       |                            |
|              |                     |         | 175/65R14     |                       |                            |

**Prüfbericht 22-00097-CX-GBM-02**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058**

**ANLAGE: 9.6**  
 Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18  
 Stand: 17.07.2023



Auto Service

Seite: 2 von 4

commercial type: **CITIGO**

| Vehicle type | Approval            | kW      | Tires        | Restrictions of tires | Restrictions   |
|--------------|---------------------|---------|--------------|-----------------------|--|
| AAN          | e13*2007/46*1184*.. | 44 - 55 | 165/70R14    | 12K; 51G              | 10B; 11H; 11N; 51A;<br>744; 76V; BF2; 1);<br>2); 33) |
|              |                     |         | 175/65R14    | 51G                   |  |
| AAN          | e13*2007/46*1184*.. | 55      | 165/70R14 81 |                       | 744; BF2; 1); 2);<br>33)                             |
|              |                     |         | 175/65R14 82 |                       |  |

**Manufacturer : SEAT, SKODA, VOLKSWAGEN**

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

Tightening torque for fixing parts : 110 Nm

commercial type: **UPI**

| Vehicle type | Approval            | kW      | Tires         | Restrictions of tires | Restrictions   |
|--------------|---------------------|---------|---------------|-----------------------|--|
| AA           | e13*2007/46*1167*.. | 60 - 61 | 165/70R14 M+S |                       | 744; 77E; BF2; 1);<br>2); 33)  |
| AA           | e13*2007/46*1167*.. | 44 - 66 | 165/70R14     | 12K; 51G              | 10B; 11H; 11N; 51A;<br>744; 76V; 77E; BF2;<br>1); 2); 33)                |
|              |                     |         | 175/65R14     | 51G                   |  |
| AA           | e13*2007/46*1167*.. | 60      | 165/70R14 M+S | 12K; 51G; 52J         | *) ; e-up!;<br>10B; 11H; 11N; 51A;<br>76V; BF2; 1); 2);<br>33)           |
| AA           | e13*2007/46*1167*.. | 60      | 165/70R14 M+S |                       | 744; 77E; BF2; 1);<br>2); 33)  |
| AA           | e13*2007/46*1167*.. | 55      | 165/70R14     |                       | 744; 77E; BF2; 1);<br>2); 33)  |
|              |                     |         | 175/65R14     |                       |  |
| AA           | e13*2007/46*1167*.. | 55      | 165/70R14     |                       | 744; 77E; BF2; 1);<br>2); 33)  |
|              |                     |         | 175/65R14     |                       |  |
| AA           | e13*2007/46*1167*.. | 44 - 50 | 175/65R14     |                       | 744; 77E; BF2; 1);<br>2); 33)  |
|              |                     |         | 165/70R14     |                       |  |
|              |                     | 44 - 61 | 165/70R14 M+S |                       |  |
| AA           | e13*2007/46*1167*.. | 44 - 55 | 165/70R14     |                       | 744; 77E; BF2; 1);<br>2); 33)  |
|              |                     |         | 175/65R14     |                       |  |
|              |                     | 66      | 165/70R14     |                       |  |
|              |                     |         | 175/65R14     |                       |  |
| AA           | e13*2007/46*1167*.. | 44 - 66 | 165/70R14     |                       | 744; 77E; BF2; 1);<br>2); 33)  |
|              |                     |         | 175/65R14     |                       |  |
|              |                     | 55 - 66 | 165/70R14 M+S |                       |  |
| AA           | e13*2007/46*1167*.. | 60      | 165/70R14 M+S |                       | 744; 77E; BF2; 1);<br>2); 33)  |
| AAN          | e13*2007/46*1182*.. | 60      | 165/70R14 M+S |                       | 744; 77E; 1); 2);<br>33)   |
| AAN          | e13*2007/46*1182*.. | 60      | 165/70R14 M+S | 12K; 51G; 52J         | *) ; e-up!;<br>10B; 11H; 11N; 51A;<br>744; 76V; 77E; BF2;<br>1); 2); 33) |

**Prüfbericht 22-00097-CX-GBM-02**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058**

**ANLAGE: 9.6**  
 Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18  
 Stand: 17.07.2023



Auto Service

Seite: 3 von 4

commercial type: **UPI**

| Vehicle type | Approval            | kW      | Tires                  | Restrictions of tires | Restrictions  |
|--------------|---------------------|---------|------------------------|-----------------------|---|
| AAN          | e13*2007/46*1182*.. | 44 - 55 | 165/70R14<br>175/65R14 | 12K; 51G<br>51G       | 10B; 11H; 11N; 51A;<br>744; 76V; 77E; BF2;<br>1); 2); 33) |
| AAN          | e13*2007/46*1182*.. | 44 - 55 | 165/70R14<br>175/65R14 |                       | 744; 77E; BF2; 1);<br>2); 33)                             |
| AAN          | e13*2007/46*1182*.. | 44 - 55 | 165/70R14<br>175/65R14 |                       | 744; 77E; BF2; 1);<br>2); 33)                             |
| AAN          | e13*2007/46*1182*.. | 60      | 165/70R14 M+S          |                       | 744; 77E; BF2; 1);<br>2); 33)                             |

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

### Restrictions

- 10B) Apart from tires with an M + S tread, the required minimum speed ranges for the tires to be used, taking load indexes into consideration, can be found in the vehicle documentation, unless deviations have been defined in the scope of application.
- 11H) If the standard spare wheel is used, the car should be driven at moderate speed and for no longer than necessary. The wheel must be fitted with standard fastening elements. When the spare wheel is used on four-wheel-drive vehicles, care should be taken to use only tires with identically sized rolling circumference.
- 11N) The brake and steering systems and the suspension, except for custom suspension springs, must be standard, unless governed by other requirements.
- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51A) The inflation pressure specified by the vehicle manufacturer (see operating instructions or tire inflation pressure indicated on the vehicle) or tire manufacturer must be observed. According to the manufacturer, tires with run-flat properties may only be used in combination with a tire inflation monitoring system.
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 52J) This tire size is only permitted with M+S tread
- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 76V) The use of this tire size and offset is only permitted if used as standard.
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- BF2) The use of the wheels is not permitted on vehicle versions with brake disc diameter 288mm or larger on the front axle.
- 1) To be kept:  
 - the standard wheel size and offset.  
 - tyre size with service description (load and speed index) and tyre brand commitments

**Prüfbericht 22-00097-CX-GBM-02**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058**

**ANLAGE: 9.6**

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 4 von 4

- as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.