

Prüfbericht 22-00175-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000831

ANLAGE: 9.7

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 29.09.2022



Auto Service

Seite: 1 von 3

Manufacturer : CITROEN, PEUGEOT**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 23

Hole circle (mm)/number of holes : 108/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1651	R1-1651	Without	65		525	1937	04/22

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : CITROENMounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : SH; S****; SH****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type :
SH****; D; SH8FN; S; S*8FN; SH

Tightening torque for fixing parts : 100 Nm

commercial type: **CITROEN C-ELYSEE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
D	e2*2007/46*0225*..	53 - 85	185/65R15		1); 2); 33)

commercial type: **CITROEN C3, DS3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S****	e2*2007/46*0003*..	44 - 88	185/65R15 88		*) ; 3-door; 5-door; 1); 2); 33)

commercial type: **CITROEN C3, DS3, DS3 CABRIO,**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S	e2*2007/46*0003*..	81	185/65R15		744; 77E; 1); 2); 33)
S	e2*2007/46*0003*..	44 - 88	185/65R15 81		77E; 1); 2); 33)
			185/65R15 88		
			185/65R15-88H		

commercial type: **CITROEN C3 PICASSO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
SH	e2*2001/116*0371*..	66 - 70	195/60R15 88		1); 2); 33)
SH****	e2*2001/116*0371*..				
SH8FN	e24*2007/46*0029*..	67 - 70	195/60R15 88		1); 2); 33)

Prüfbericht 22-00175-CX-GBM-05**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000831****ANLAGE: 9.7**

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 29.09.2022



Auto Service

Seite: 2 von 3

commercial type: **CITROEN DS3, C3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S*8FN	e24*2007/46*0028*..	67 - 70	185/65R15		*) ; C3; 744; 1); 2); 33)
S*8FN	e24*2007/46*0028*..	44 - 88	185/65HR15		1); 2); 33)

Manufacturer : CITROEN, PEUGEOT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PEUGEOTMounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : W*****

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : D; CTightening torque for fixing parts : 90 Nm for Type : W*****
100 Nm for Type : C; Dcommercial type: **PEUGEOT 207**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
W*****	e2*2001/116*0340*..	50 - 70	185/65R15 88		*); not Escapade (Ausf. WU****); 1); 2); 33)
		50 - 88	185/65R15-88H		
W*****	e2*2001/116*0340*..	50 - 70	185/65R15 88		*); not Escapade (Ausf. WU****); not convertible; Front wheel drive; not with increased chassis clearance; 1); 2); 33)
		50 - 88	185/65R15-88H		

commercial type: **PEUGEOT 208, 2008**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
C	e2*2007/46*0070*..	50 - 88	185/65R15		77E; 1); 2); 33)

commercial type: **PEUGEOT 301**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
D	e2*2007/46*0224*..	53 - 85	185/65R15 80		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.

77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.

Prüfbericht 22-00175-CX-GBM-05

zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000831

ANLAGE: 9.7

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 29.09.2022



Auto Service

Seite: 3 von 3

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.