

Prüfbericht 20-00295-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 1 von 2

Manufacturer : FORD**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 52,5

Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1557	R1-1557	Without	63,35		610	1930	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 100 Nm for Type : BWY; B4Y; B5Y; DA3; DB3

120 Nm for Type : DA3

120 Nm (Nur C-MAX) for Type : DM2

commercial type: **FOCUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DA3	e13*2001/116*0144*..	59 - 107	205/55R16		1); 2); 33)
DA3	e13*2001/116*0144*..	59 - 107	205/55R16		1); 2); 33)
		85 - 166	205/55R16 M+S		
DB3	e13*2001/116*0157*..	59 - 74	205/55R16 84		*); only to e13*2001/116*0157*08; Convertible; notchback; 1); 2); 33)
		66 - 80	205/55R16-85		
		80	205/55R16-86		
		85	205/55R16 84H		
			205/55R16-86H		
		85 - 107	205/55R16 M+S		
		92	205/55R16 84V		
		98 - 100	205/55R16 87V		
		107	205/55R16 85V		

commercial type: **FORD C-MAX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2	e13*2001/116*0109*..	66 - 107	205/55R16		*); Only C-MAX; 1); 2); 33)
		80 - 107	205/55R16 M+S		
		100	205/55R16-88H		
		107	205/55R16 87V		

Prüfbericht 20-00295-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840

ANLAGE: 9.1
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45
 Stand: 02.08.2023



Auto Service

Seite: 2 von 2

commercial type: **FORD MONDEO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
BWY	e1*98/14*0156*..	66 - 150	205/50R16		1); 2); 33)
			205/55R16		
		66 - 166	205/55R16 89 M+S		
B4Y	e1*98/14*0154*..	66 - 150	205/55R16		1); 2); 33)
		66 - 166	205/55R16		
		85 - 150	205/50R16		
B5Y	e1*98/14*0155*..	66 - 150	205/50R16		1); 2); 33)
			205/55R16		
		66 - 166	205/55R16		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.