

**Prüfbericht 21-00319-CX-GBM-07**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847**

**ANLAGE: 9.15**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62  
 Stand: 21.04.2022



Auto Service

Seite: 1 von 1

**Manufacturer : KIA MOTORS (SK)**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 40  
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-2095	R1-2095	Without	67		525	1989	30/21

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : KIA MOTORS (SK)**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad  
 Tightening torque for fixing parts : 120 Nm

commercial type: **Ceed, ProCeed, XCeed**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
CD	e4*2007/46*1299*..	77 - 150	205/60R16		MAO; 1); 2); 33)

**Restrictions**

MAO) The use of wheels on vehicle models with a brake disk diameter of 320 mm on the front axle is not allowed.

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.